




ADSYSTEMS™
HIGH PERFORMANCE DOORS



AUTOMOTION™
Sliding Door

specADsystems.com



SETTING THE FUTURE IN MOTION

AD Systems is constantly perfecting the art and functionality of the sliding door, and our innovation continues to be ... automatic. Our latest product offering meets our clients' needs for acoustic isolation and space-saving design, along with the added benefit of easy, hands-free access.

Introducing AutoMotion™ sliding doors. This revolutionary door system is quiet, safe, easy to install, efficient, durable, and flexible thanks to a wide variety of accessories.

Standard Features

AUTOMOTION DOOR OPERATOR

- Low Energy Operator for safety and accessibility
- Advanced **BRUSHLESS** motor and worm gear integration for quiet, reliable efficiency
- Operates on a wide range of power input
- Safety sensors ensure safe passage through doorway
- Low noise drive unit provides a simple and convenient installation
- Standard kit allows for installation of a single door or a bi-parting pair
- Microcomputer intelligent control and advanced mechanical configuration
- Low power consumption, and an energy-saving standby mode
- Optional battery backup keeps the door working normally during a power outage
- The high torque motor provides rapid speed up and slow down with a long service life
- Additional accessories available such as 4-function remote control, function keypad, touchless door actuator, interior and exterior sensors, etc.

Additional Accessories

- 4-function remote control
- Function keypad
- Touchless door actuator
- Interior/exterior sensors



Specifications

DOOR LEAF MODE	SINGLE OPENING	DOUBLE OPENING
Door Leaf Weight (AD-155)	Max 264 lbs.	Max 2 x 264 lbs.
Door Leaf Width	27.5 – 51.2 in.	23.6 – 49.2 in.
Electrical Service	100–230VAC @ 50/60Hz, 5 amps	
Opening Speed	0.5 – 1.5 feet / sec. (Adjustable)	
Closing Speed	0.3 – 1.4 feet / sec. (Adjustable)	
Opening Time	0 – 9 second (Adjustable)	
Manual Open Force *in power OFF mode	< 9lbs	< 11lbs
Motor	24V, 55W brushless DC motor	
Operating Temp.	-4°F – +158°F	



ADSYSTEMS™ ALLEGION® 

specADsystems.com | 425.740.6011 | ADsystems.Sales@allegion.com

062121